



The MINOR blower as an air supply for the DIODE PID.

MINOR: The mobile air supplier.

Don't be deceived by the MINOR's small size and low weight. This blower delivers sufficient air to enable quality work with the DIODE PID / DIODE S or LABOR S.

Accessories DIODE PID / DIODE S

With push-fit nozzle

	100.303 Ø 5 mm tubular nozzle, for versions with nozzles, push-fit
	106.992 Speed welding nozzle, push-fit on Ø 5 mm tubular nozzle 5.7 mm, profile A 106.993 7 mm, profile B
	106.989 3 mm 106.990 4 mm 106.991 5 mm
	106.996 Tacking nozzle, push-fit on Ø 5 mm tubular nozzle
	143.833 Nozzle adapter for screw-on nozzles
	100.296 Heating element DIODE PID, 230 V / 1550 W 100.650 Heating element DIODE PID, 120 V / 1600 W 100.689 Heating element DIODE S, 230 V / 1550 W 100.702 Heating element DIODE S, 120 V / 1600 W

With screw-on nozzle

	105.622 Ø 5 mm tubular nozzle, screw-on
	106.988 Tacking nozzle, screw-on
	113.666 Ø 3 mm round drawing nozzle with tacking tip, screw-on
	113.399 Ø 4 mm round drawing nozzle, with tacking tip, screw-on
	113.876 Ø 3 mm round drawing nozzle without tacking tip, screw-on
	113.874 Ø 4 mm round drawing nozzle, without tacking tip, screw-on
	113.670 Triangular drawing nozzle, with tacking tip, screw-on, 5.7 mm
	113.877 Without tacking tip, screw-on 5.7 mm, profile A
	106.986 Without tacking tip, screw-on 7 mm, profile B
	106.987 7 x 5.5 mm
	126.552 4 mm drawing nozzle, screw-on, for fluoroplastics
	141.375 Connection adapter M14 for Ø 21.3 mm nozzle with plug

Blower

MINOR



- Lightweight and compact
- Powerful
- Serves as a mobile air supply for the DIODE PID / DIODE S and LABOR S
- Suitable for work on construction sites

Technical data

Voltage	V~	230
Power	W	100
Air volume (20°C)	l/min	400
Pressure static	Pa	4000 (40 mbar)
Air outlet (external)	mm	14.5
Size (L x Ø)	mm	250 x 95, handle Ø 64
Weight	kg	1.15 (with 3 m cord)
Conformity mark	CE	
Approval mark		
Protection class II		

Article No.:

108.747	MINOR, 230 V / 100 W, with Euro plug
109.988	MINOR, 120V / 100W, with UK plug

Additional versions available upon request